



UPPER FORK



CBD30-170HA

3.0T Electric Jack Pallet



UPPER FORK

PARAMETERS & PERFORMANCE

CBD30-170HA

FEATURE

Model	CBD30-170HA	
Operating type	Pedestrian	
Load capacity	kg	300
Load center	mm	600
Wheel base	mm	1380

WHEELS

Wheels type	Driving:Rubber Bearing:Nylon	
Driving wheel/Bearing wheel	1X+0/4	
Driving wheel size	mm	Φ300x110
Bearing wheel size	mm	Φ84x80

DIMENSION

Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Outside width between forks	mm	560/685
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	75
Overall length	mm	1723/1773
Overall width	mm	697
Overall height(with handle)	mm	1382
Overall height(Without handle)	mm	838
Min.Turning radius	mm	1578/1628
Min.Aisle width for pallets 800X 1200	mm	1883/1933
Min.Aisle width for pallets 1000X 1200	mm	1911/1961

PERFORMANCE

Travel speed,laden/unladen	km/h	3.5/4
Lift speed,laden/unladen	mm/s	17/23
Lowering speed,laden/unladen	mm/s	35/30
Gradeability,laden/unladen	%	6/16
Service brake type	Electric	

ELECTRICAL CONFIGURATION

Traction motor rating at S2 60 min	KW	BLDC1.8	
Lift motor rating at S3 15%	KW	DC 0.8	
Battery voltage/ capacity	V/Ah	48/30(VRLA)	48/65(Optional)
Charger specification	V/A	48/5	48/9

WEIGHT

Battery weight(±5%)		9×4	15×4
Service weight with battery	kg	336	360

OTHERS

Steering type	Mechanical		
Drive controltype	BLDC		